FRSC Chemical Solutions

SAFETY DATA SHEET

1. Identification

Product identifier Battery Terminal Cleaner

Other means of identification

Part No. BTC6

Recommended useCleans battery terminals, connectors, battery tray, holder bolts and brackets.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name
Address
RSC Chemical Solutions
600 Radiator Road
Indian Trail, NC 28079

United States

Telephone Customer Service: (704) 821-7643

Technical: (704) 684-1811

Website www.rscbrands.com
E-mail sds@rscbrands.com

Emergency phone number Emergency Telephone: (303) 623-5716

Emergency Contact: RMPDC (877-740-5015)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, dermal Category 1
Acute toxicity, inhalation Category 4

Germ cell mutagenicity

Classification not possible

Carcinogenicity

Classification not possible

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Harmful if swallowed. Fatal in contact with skin. Harmful if inhaled. May cause damage to organs

through prolonged or repeated exposure.

Precautionary statement

Prevention Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Wash thoroughly after

handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a

well-ventilated area. Wear protective gloves/protective clothing.

Response If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. Rinse mouth. Take off immediately all contaminated clothing and wash it

Category 2

before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise None known.

classified (HNOC)

Material name: Battery Terminal Cleaner BTC6 Version #: 01 Issue date: 08-17-2015

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	3 - < 5
Isobutane		75-28-5	3 - < 5
Sodium Bicarbonate		144-55-8	3 - < 5
Propane		74-98-6	1 - < 3
Other components below reportable leve	ls		80 - < 90

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Wash off with soap and water. Call a physician or Skin contact poison control center immediately. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting without Ingestion advice from poison control center. If vomiting occurs, keep head low so that stomach content

doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

Prolonged exposure may cause chronic effects.

Most important symptoms/effects, acute and delayed

Indication of immediate

medical attention and special treatment needed General information

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Take off immediately all contaminated clothing. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Discard any shoes or clothing items that cannot be decontaminated.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media Specific hazards arising from

During fire, gases hazardous to health may be formed.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Containers should be cooled with water to prevent vapor pressure build up.

Specific methods General fire hazards

equipment/instructions

the chemical

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Battery Terminal Cleaner SDS US 2/10

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
·		50 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Isobutane (CAS 75-28-5)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA),	Creatinine in urine	*
		with hydrolysis		

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke. Keep away from food and drink. Always observe good personal

considerations hygiene measures, such as washing after handling the material and before eating, drinking, and/or

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Liquid. **Appearance** Liquid. Physical state

Form Aerosol.

Color Yellow-orange.

Mild. Characteristic odor Odor

Not available. Odor threshold

8 - 9

Melting point/freezing point Not available.

Initial boiling point and boiling

range

> 200 °F (> 93.33 °C)

Flash point > 220.0 °F (> 104.4 °C) Tag Closed Cup

Evaporation rate < 1 Butyl Acetate = 1

Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

0.00001 hPa estimated Vapor pressure

Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Soluble

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

BTC6 Version #: 01 Issue date: 08-17-2015

SDS US

Decomposition temperature Not available.

Viscosity < 5 cSt

Other information Aerosol foam

Flame height 7 in

Density 9.11 lbs/gal estimated

Explosive properties Not explosive. **Flame extension** Non-Flammable

Flammability per Flame Projection Test Not Flammable

Flammability class Combustible IIIB estimated

Heat of combustion 4 kJ/g

Heat of combustion (NFPA

30B)

3.05 kJ/g estimated

Oxidizing properties Not oxidizing.

Percent volatile 92.4 %

Specific gravity 1.04 - 1.07

1

VOC (Weight %) 9.7 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure by

inhalation.

Skin contact Fatal in contact with skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Fatal in contact with skin. Harmful if inhaled. Harmful if swallowed.

Components Species Test Results

2-Butoxyethanol (CAS 111-76-2)

Acute Dermal

LD50 Rabbit 400 mg/kg

Inhalation

LC50 Mouse 700 ppm, 7 Hours

Rat 450 ppm, 4 Hours

Components	Species	Test Results
Oral		
LD50	Guinea pig	1.2 g/kg
	Mouse	1.2 g/kg
	Rabbit	0.32 g/kg
	Rat	560 mg/kg
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	52 mg/l, 1 Hours
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
Sodium Bicarbonate (CAS 144-55-8)		
<u>Acute</u>		
Oral		
LD50	Rat	4220 mg/kg

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects May cause damage to organs through prolonged or repeated exposure. May be harmful if

absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

2-Butoxyethanol (CAS 111-76-2)

Aquatic

Fish LC50 Inland silverside (Menidia beryllina) 1250 mg/l, 96 hours

Components **Species Test Results**

Sodium Bicarbonate (CAS 144-55-8)

Aquatic

Fish LC50 Western mosquitofish (Gambusia affinis) 7550 mg/l, 96 hours

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-Butoxyethanol 0.83 2.76 Isobutane Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

14. Transport information

DOT

Not available. **UN number**

UN proper shipping name

Consumer Commodity

Transport hazard class(es)

ORM-D

Subsidiary risk

Not applicable. Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, Non-Flammable

2.2 Class Subsidiary risk

Not applicable.

Environmental hazards

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Packing group

Forbidden.

Cargo aircraft only Forbidden.

IMDG

UN1950 **UN number**

UN proper shipping name

Aerosols, Non-Flammable

Transport hazard class(es)

Class 2.2 Subsidiary risk

Packing group Not applicable.

^{*} Estimates for product may be based on additional component data not shown.

Environmental hazards

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code IATA; IMDG



15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2) Listed. Isobutane (CAS 75-28-5) Listed. Propane (CAS 74-98-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 2-Butoxyethanol
 111-76-2
 3 - < 5</td>

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

2-Butoxyethanol (CAS 111-76-2) Isobutane (CAS 75-28-5)

US. Massachusetts RTK - Substance List

2-Butoxyethanol (CAS 111-76-2)

Isobutane (CAS 75-28-5)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

2-Butoxyethanol (CAS 111-76-2) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-Butoxyethanol (CAS 111-76-2) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

US. Rhode Island RTK

2-Butoxyethanol (CAS 111-76-2) Isobutane (CAS 75-28-5) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-17-2015

Version # 01

HMIS® ratings Health: 1

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 1

Flammability: 1 Instability: 0

NFPA ratings



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Material name: Battery Terminal Cleaner BTC6 Version #: 01 Issue date: 08-17-2015