Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

PREMIUM CONVENTIONAL 5W-30

Motor Oil

Details of the supplier of the safety data sheet Valvoline LLC

100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825) Emergency telephone number

+1-800-VALVOLINE (+1-800-825-8654)

Regulatory Information Number 1-800-TEAMVAL (1-800-8326-825)

Product Information

1-800-TEAMVAL (1-800-8326-825)

SDS@valvoline.com

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards which do not result in classification

No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Chemical nature

: Defatter

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
Lubricating oils (petroleum), hydrotreated	64742-58-1	Not a hazardous substance or mixture.	>= 70.00 - < 90.00
PETROLEUM DISTILLATES	64742-54-7	Asp. Tox. 1; H304	>= 1.00 - < 10.00
Reaction products of Benzeneamine N-phenyl- with	36878-20-3	3; H316	>= 1.00 - < 10.00

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

nonene (branched)	Aquatic Chronic 4; H413	

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

: No hazards which require special first aid measures. Notes to physician

Valvoline.	Page: 3
SAFETY DATA SHEET	Revision Date: 09/15/2017
_	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

nitrogen oxides (NOx)

Specific extinguishing

methods

: Standard procedure for chemical fires.

Product is compatible with standard fire-fighting agents.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

Environmental precautions

: Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion

: Normal measures for preventive fire protection.

Advice on safe handling

: Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Materials to avoid

: No materials to be especially mentioned.

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
PETROLEUM DISTILLATES	64742-54-7	CMP (Mist)	5 mg/m3 Mist	AR OEL
		CMP - CPT (Mist)	10 mg/m3 Mist	AR OEL
		TWA (Mist)	5 mg/m3 Mist	PE OEL
		STEL (Mist)	10 mg/m3 Mist	PE OEL
		L-8/40 (Mist)	5 mg/m3 Mist	VE OEL
		LB (Mist)	10 mg/m3 Mist	VE OEL
		CPT (Mist)	5 mg/m3 Mist	PA OEL
		CCT (Mist)	10 mg/m3 Mist	PA OEL
		TWA (Mist, inhalable)	5 mg/m3 Mist, inhalable	CR OEL
		STEL (Mist)	10 mg/m3 Mist	CR OEL

Engineering measures

: General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally

required.

Eye protection

: Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection

: Wear as appropriate:

Safety shoes

Hygiene measures

: General industrial hygiene practice.

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

Physical state

: liquid

Odour

: No data available

Odour Threshold

: No data available

pН

: No data available

Melting point/freezing point

: No data available

Boiling point/boiling range

: No data available

Flash point

: > 199 °CMethod: Cleveland open cup

Evaporation rate

: No data available

Flammability (solid, gas)

: No data available

Upper explosion limit

: 6 %(V)

Calculated Explosive Limit

Lower explosion limit

: 1 %(V)

Calculated Explosive Limit

Calculated Vapor Pressure

: 1.3333333 hPa (20 °C)

Relative vapour density

: No data available

Relative density

Vapour pressure

: 0.876 (15.6 °C)

Density

: 0.8599 g/cm3 (15.6 °C)

Solubility(ies)

Water solubility

: No data available

Solubility in other solvents

: No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition

No data available

Viscosity

Viscosity, dynamic

: No data available

Viscosity, kinematic

: 63 mm2/s (40 °C)

Oxidizing properties

: No data available

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No decomposition if stored and applied as directed.

Chemical stability

: Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid

: None known.

Incompatible materials

: Strong oxidizing agents

Hazardous decomposition

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Lubricating oils (petroleum), hydrotreated:

Acute oral toxicity

: LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Acute dermal toxicity

: LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

PETROLEUM DISTILLATES:

Acute oral toxicity

: LD50 (Rat): > 15 g/kg

Acute dermal toxicity

: LD50 (Rabbit): > 5 g/kg

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity

: LD50 (Rat): > 5,000 mg/kg

Acute dermal toxicity

: LD50 (Rat): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Valvoline	Page: 7
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

Lubricating oils (petroleum), hydrotreated:

Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

PETROLEUM DISTILLATES:

Result: Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: Rabbit

opecies. Nabbit

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Lubricating oils (petroleum), hydrotreated:

Result: Slight, transient irritation

PETROLEUM DISTILLATES:

Result: No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

PETROLEUM DISTILLATES:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Lubricating oils (petroleum), hydrotreated:

Toxicity to daphnia and other : LC50 (Brine shrimp (Artemia salina)): > 22,500 mg/l

aquatic invertebrates Exposure time: 48 h

Valvoline	Page: 9
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

Chronic aquatic toxicity : No toxicity at the limit of solubility

PETROLEUM DISTILLATES:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Fish): 10 mg/l

aquatic invertebrates Chronic toxicity)

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l Toxicity to algae

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

No data available

Persistence and degradability

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

: Result: Not readily biodegradable. Biodegradability

> Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-: log Pow: > 7.5

octanol/water

Valvoline	Page: 10
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging

: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

UN DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Chemical Control Order (CCO) : Not applicable

Priority Chemical List (PCL) : Not applicable

Hazardous Substance Act B.E. 2535 : Not applicable

Emergency Decree on Controlling the Use of Volatile : Not applicable

Substances B.E. 2533

Other international regulations

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

IECSC : q (quantity restricted)

PICCS : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 09/15/2017

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H316 Causes mild skin irritation.

H413 May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their piratespace. This SDS has been prepared by

to their circumstances. This SDS has been prepared by

Page: 12
Revision Date: 09/15/2017
Print Date: 1/16/2018
SDS Number: R0172013
Version: 3.0

800-VALVOLINE).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL: Occupational Exposure Limit
P-Statement: Precautionary Statement
PBT: Persistent, Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value TWA : Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CEATOX

Assistance Center of the Institute of Toxicology Children's Hospital Clinic, Faculty of Medicine University of São Paulo.

BR OEL : Occupational Exposure Limit (Brazil)

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 09/15/2017
	Print Date: 1/16/2018
	SDS Number: R0172013
PREMIUM CONVENTIONAL 5W-30 Motor Oil	Version: 3.0
3081	

PY OEL : Occupational Exposure Limit (Paraguay)