# SAFETY DATA SHEET

## 1. Identification of the substance/mixture and of the company

#### 1.1 Product identifier

# Product Name: Type RP<sup>™</sup> Rapid Power Electrical Cleaning Wipe

Product ID numbers: RP-1, RP-1L

RP-XXX (Where XXX is the package code.)

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses:

Utility Cleaner/Degreaser

List of advices against:

Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

**American Polywater Corporation** 

11222 - 60th Street North Stillwater, MN 55082 USA

Tel: 1-651-430-2270

Email: sds@polywater.com

Polywater Europe BV

Zuidhaven 9-11 Unit B2 4761 CR Zevenbergen

Netherlands

Tel: +31 (0)10 2330578 Email: sds@ polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

#### 2. Hazards Identification

## 2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Flam Liq 2

H225

Skin Irrit, 2

H315

STOT SE 3

H336

2.2 Label elements

Contains:

2-methylpentane, Low boiling point naphtha, 1-methoxypropan-2-ol



Pictograms:

Signal word:

Danger

Hazard Statements:

H225

Extremely flammable liquid and vapor

H315

Causes skin irritation.

H336

May cause drowsiness or dizziness

**Precautionary Statements:** 

P210

Keep away from sparks, flames and hot surfaces. No smoking.

P261

Avoid breathing vapor.

P280

Wear protective gloves.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

P304 + P340

breathing.

IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water.

Revision Date: April 23, 2015

P353

P303 + P361 +

P370 + P378 In case of fire: Use water fog, foam, dry chemical or carbon dioxide for extinction.

Store in a well-ventilated place. Keep cool. P403 + P235

Aspiration classification not applied due to the physical form of the product. Notes:

No information available. 2.3 Other hazards:

## 3. Composition/Information on Ingredients

| Component<br>2-methylpentane | <u>CAS #</u><br>107-83-5 | EC #<br>203-523-4 | Wt. %<br>40 - 60% | GHS/CLP Classification<br>Flam Liq 2, H225;<br>Asp Tox 1, H304; |
|------------------------------|--------------------------|-------------------|-------------------|---|
|                              |                          |                   |                   | Skin Irrit 2, H315<br>STOT SE 3, H336                           |
| Low boiling point naphtha    | 64742-89-8               | 265-192-2         | 40 - 60%          | Flam Liq 2, H225;<br>Asp Tox 1, H304;<br>Skin Irrit 2, H315     |
| 1-methoxypropan-2-ol         | 107-98-2                 | 203-539-1         | <10%              | STOT SE 3, H336<br>Flam Liq 3, H226;<br>STOT SE 3, H336         |

#### 4. First Aid Measures

## 4.1 Description of first aid measures

**Eye Contact:** 

If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Remove contaminated clothing: flush skin thoroughly with water. If irritation Skin Contact:

occurs, seek medical attention.

If irritation of nose or throat develops, move to fresh air. If irritation persists, seek Inhalation (Breathing):

medical attention. If breathing is difficult, provide oxygen. If not breathing, give

artificial respiration. Seek immediate medical attention.

Do not induce vomiting or give anything by mouth unless directed to do so by Ingestion (Swallowing):

medical personnel. Get medical attention if symptoms appear.

# 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

# 4.3 Indication of immediate medical attention and special treatment needed.

No information available.

# 5. Firefighting Measures

# 5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

#### 5.2 Special hazards arising from the substance or mixture

## Hazardous decomposition and by-products:

Burning generates carbon monoxide, carbon dioxide.

#### 5.3 Advice for firefighters

Wear appropriate, protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers.

## 6. Accidental Release Measures

## 6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

#### 6.2 Environmental precautions:

Avoid release to the environment.

## 6.3 Methods materials for containment and cleaning up:

Collect towel and absorb any excess material with sand or absorbents.

#### 6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

## 7. Handling and Storage

#### 7.1 Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use only outdoors or in a well-ventilated area. For industrial or professional use only.

## 7.2 Conditions for safe storage, including incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

#### 7.3 Specific end uses

See technical data sheet on this product for further information.

## 8. Exposure Controls / Personal Protection

#### 8.1 Control parameters

#### Exposure limits and recommendations:

| Component Name                                    | Limit                     |                         | Standard    | Source/Note |  |  |
|---|---------------------------|-------------------------|-------------|-------------|--|--|
| 2-methylpentane                                   | TLV                       | 500 ppm<br>100 ppm      | ACGIH, OSHA | USA         |  |  |
| Low boiling point naphtha<br>1-methoxypropan-2-ol | TLV                       | 1,800 mg/m <sup>3</sup> | NIOSH       | USA         |  |  |
|   | STEL                      | 1,000 ppm               | ACGIH, OSHA |             |  |  |
|   | No information available. |                         |             |             |  |  |
|   | TWA                       | 100 ppm                 | ACGIH       | USA         |  |  |
|   | STEL                      | 150 ppm                 | ACGIH       | USA         |  |  |

#### 8.2 Exposure controls

## Respiratory protection:

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH-approved) or use supplied air equipment.

## Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material:

Nitrile Rubber

For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use

Suggested Thickness: 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material. Maximum wearing time should be determined based on 50 % of the penetration time determined by EN

Revision Date: April 23, 2015

374 part III.

## Eye protection:

Safety glasses recommended.

#### Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

## 9. Physical and Chemical

#### 9.1 Information of basic physical and chemical properties

Appearance:

Clear, colorless liquid; mild odor.

Odor threshold:

Not available

pH:

Does not apply

Freezing point:

Not available

**Boiling point:** 

144°F / 62°C (initial)

Flash point:

19°F / -7°C (TCC)

Evaporation rate:

>2 (n-butyl acetate = 1)

Flammability (solid, gas):

Not applicable to liquids

Flammability limits:

LEL: 1.2%

Vapor pressure:

Not available

Vapor density (Air = 1):

>1(Air = 1)

Specific gravity (H<sub>2</sub>O = 1):

0.72

Solubility in water:

Not available

Coefficient of Water/Oil

Distribution:

Not available

Auto-ignition temperature:

Not available

Decomposition temperature:

Not available

Viscosity:

Not available

9.2 Other Information

Volatiles (Weight %):

100%

**VOC Content:** 

720 g/l

#### 10. Stability and Reactivity

## 10.1 Reactivity:

See remaining headings in Section 10.

# 10.2 Chemical stability:

Stable

#### 10.3 Possibility of hazardous reactions:

None known.

#### 10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

#### 10.5 Incompatible materials:

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

## 11. Toxicological Information

Revision Date: April 23, 2015

Product Name: Type RP<sup>™</sup> Rapid Power Electrical Cleaner Revision Date: April 23, 2015

## 11.1 Information on toxicological effects:

#### Acute toxicity

#### Eye contact:

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

#### Skin contact

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

#### Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

## Inhalation (Breathing):

Concentrated solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

## Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

## **Toxicity to Animals:**

2-methylpentane

No Data Available

Low boiling point naphtha

LD<sub>50</sub> (oral rat) >5,000 mg/kg

LD<sub>50</sub> (dermal rabbit) >2,000 mg/kg

Rabbit 4 hr exposure: Irritating to skin, irritating to eyes

1-methoxypropan-2-ol

LD<sub>50</sub> (oral rat) 6,100 mg/kg

LD<sub>50</sub> (dermal rabbit) 13,000 mg/kg

LC<sub>50</sub> (inhl rat) >6 mg/l

Chronic Exposure:

Reproductive Toxicity:

No data available.

Mutagenicity:

No data available

Teratogenicity:

Specific Target Organ

Toxicity (STOT)

No data available

Toxicologically Synergistic

Products:

No end point data.

Not available.

Carcinogenic Status:

IARC

No components of this product present at levels greater than or equal to 0.1%

is identified as a carcinogen or potential carcinogen by IARC.

OSHA No components of this product present at levels greater than or equal to 0.1%

is identified as a carcinogen or potential carcinogen by OSHA.

NTP No components of this product present at levels greater than or equal to 0.1%

is identified as a known or anticipated carcinogen by NTP.

#### 12. Ecological Information

12.1 Ecotoxicity:

Aquatic Toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

2-methylpentane No Data Available

Low boiling point naphtha 96 h LC<sub>50</sub> Oncorhynchus mykiss (Rainbow Trout) 8.2 mg/l

48 h EC<sub>50</sub> Daphnia magna (water flea) 4.5 mg/l

96 h EC<sub>50</sub> Pseudokirchneriella subcapitata (green algae) 3.7 mg/l

1-methoxypropan-2-ol 96 h LC<sub>50</sub> Pimephales promelas (Fathead Minnow) 20,800 mg/l

48 h LC<sub>50</sub> Daphnia magna (water flea) 23,300 mg/l

7 d EC<sub>50</sub> Pseudokirchneriella subcapitata (green algae) > 1000 mg/l

Revision Date: April 23, 2015

12.2 Persistence and degradability:

Expected to be biodegradable

Low boiling point naphtha

77% biodegradable, 28 d exposure time, method: OECD 301E

1-methoxypropan-2-ol

96% biodegradable, 28 d exposure time, method: OECD 301E

12.3 Bioaccumulation potential:

No information available

12.4 Mobility in soil:

No information available

12.5 Results of PBT and vPvB

Assessment:

This product is not, nor does it contain a substance that is a PBT or

vPvB.

12.6 Other adverse effects:

None known.

# 13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

# 14. Transport Information

**US DOT Domestic Ground** 

Transportation:

Not Regulated (See Special Provision 47).

**UN Number:** 

Solids Containing Flammable Liquid, N.O.S., (Contains: 2-methylpentane,

**UN Proper shipping name:** 

Low boiling point naphtha)

Transport hazard class(es):

Class 4.1

Packing group:

11

**Environmental hazards:** 

None known

Special precautions:

None known

ICAO/IATA-DGR:

Not Regulated (See Special Provision A46)

IMDG:

Not Regulated (See Special Provision 216)

# 15. Regulatory Information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA

Acute

Chronic

<u>Fire</u>

Pressure

Reactive

Section 311/312 Reporting

Yes

Yes

Yes

No

No

CERCLA/SARA Sec 302

**EHS TPQ** 

SARA Sec. 313

**Hazardous Substance RQ** 

**Toxic Release** 

Components are not affected by these Superfund regulations.

NFPA Ratings:

Health:

2

Fire:

3

Reactivity:

0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

#### **European Union**

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Product Name: Type RP<sup>™</sup> Rapid Power Electrical Cleaner Revision Date: April 23, 2015

#### Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

WHMIS Classification:

B<sub>2</sub>

#### Australia

All components are listed on the AICS. Hazardous according to criteria of NOHSC Australia.

#### 15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier

#### 16. Other Information

## Abbreviations and acronyms:

OSHA = Occupational Safety and Health Administration
CLP = Classification, Labeling and Packaging Regulation
STOT = Specific Target Organ Toxicity
LD<sub>50</sub> = Median Lethal Dose
DNEL = Derived No Effect Level
ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)
DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

**Revision Date:** 

April 23, 2015

Revision Number:

1

Supersedes:

Not Applicable

Other: Indication of Changes:

Created in accordance with the provisions of OSHA 1910.1200 App D and REACH

Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.